



Interior Painting

Quality Assurance Painting offers **Interior Painting** services anywhere from small painting jobs such as ceilings, doors / door frames, windows, cabinets, small rooms, to large painting jobs of kitchens, bed rooms, or any other room within a house, tilt ups, retail stores, apartment buildings and other commercial buildings. We take the necessary steps towards any interior paint job, such as caulking, patching, and proper primers to ensure that the surface is in the right condition to receive the final coat of paint. Quality Assurance Painting is a certified EPA (*Environmental Protection Agency*) painting company.

Interior Painting Surfaces

- Cabinets (*Kitchen / Bath*)
- Ceilings
- Concrete
- Crown Molding
- Baseboards
- Brick
- Doors
- Pipes
- Soffits
- Stairs
- Tile
- Trim (*includes Door Frames*)
- Walls
- Windows

Residential Interior Painting

- Cabinets (*Kitchen / Bath*)
- Ceilings
- Closets (*includes Shelves*)
- Crown Molding
- Bath Room(s)
- Baseboards
- Basement
- Bed Room(s)
- Dining Room
- Doors
- Guest Room
- Hallways
- Kitchen
- Living Room
- Stairs
- Trim (*includes Door Frames*)
- Walls
- Windows



Interior Painting

Commercial Property Interior Painting

- Apartment Buildings
- Commercial Buildings
- Industrial Buildings
- Office Buildings
- Retail Stores
- Tilt Up Buildings

**CALL TODAY
FOR A FREE ESTIMATE!
(310) 292-1192**

Processes of Interior Painting

1. Determined the area you'd like to have painted (*ceilings, walls, doors, soffits, cabinets, vanities, frames, baseboards, crown molding, etc...*).
2. First you want to scrape all imperfections, nail holes, peeling paint to prepare for paint.
3. Patch holes or imperfection with any type of spackle or interior patching material.
4. Sand all surfaces with sandpaper (*220 works best for first sand application, 320 for in between coats*).
5. Prime all surfaces with the proper primer; primer is determined by the surface. It isn't necessary to prime entire surface only where there are patches or areas that were patched, imperfection, peeling paint or if you desire you can prime all surfaces but not necessary.
6. Apply the first coat of finish material with the proper tool, typically for ceilings and walls; Standard 9 inch roller 1/4 or 1/2 inch roller nap, doors (*Mini roller works best*) baseboards and trim work.
7. Sand after first coat with 320 then wipe with a rag, apply 2nd coat.
8. Repeat as many coats as needed to achieve the results you desire.

Quality Assurance Painting - St. Lic # 845880

P.O. Box 452812, Los Angeles, CA 90045

P: (310) 292-1192 | F: (424) 257-8106 | E: ricky@qualityassurancepainting.com

www.qualityassurancepainting.com